



NFRC Certified *Window Energy Performance Ratings*



WESTERN SELECT / REHAU SERIES 100

WW Model #	Style	Test size		U-Value Clear Glass	U-Value Low-E Glass	U-Value Low-E & Argon	SHGC Clear	SHGC Low-E	SHGC Low-E W/Grid	VLT Clear Glazing	VLT Clear W/Grid	VLT Low-E	VLT Low-E W/Grid	CR Low-e	CR Low=e Argon
Western Select	SL	(60 x 36)	Res	.49	.34	.30	.62	.30	.25	.64	.58	.57	.51	54.0	57.0
Western Select	PW	(48 x 48)	Res	.49	.31	.27	.69	.33	.30	.72	.65	.63	.57	56.0	60.0
Western Select	SH	(36 x 60)	Res	.49	.34	.30	.62	.30	.25	.65	.58	.57	.51	54.0	57.0
2090P	PD	(72 x 82)	Res	.48	.33	.29	.62	.27	.25	.65	.58	.51	.45		

Note: Highlighted items are approved for 2009-2010 Stimulus Tax incentives

U-Value = Total U-Value of product

Low-E = Guardian RL 7036 soft coat low emmissivity glass (e=0.036)

SHGC = Total solar heat gain coefficient

VLT = Visible Light Transmittance

CR = Condensation resistance

All values tested/calculated with Low-E coating on surface #2 using Guardian Low-E

Patio Doors with blinds are only available with clear glass.

Current as of 10/29/2009

Sound Transmission Ratings

Window	Glazing Combination	STC Rating
110 S	SL 3/16" Clear With 1/8" Clear	31
120 S	PW 3/16" Clear With 1/8" Clear	31
130 S	SH 3/16" Clear With 1/8" Clear	32

Estimated comparison approx SS=.26

NOT certified DS=.28