



NFRC Certified *Window Energy Performance Ratings*



WW Model #	Style	Structural Rating		U-Value Clear Glass	U-Value Clear W/Argon	U-Value Low-E Glass	U-Value Low-E & Argon	SHGC Clear	SHGC Clear W/Grids	SHGC Low-E	SHGC Low-E W/Grids	VLT Clear Glazing	VLT Clear W/Grids	VLT Low-E	VLT Low-E W/Grids
Western Select	SL	(60 x 36)	Res	.49		.33	.30	.62	.56	.27	.25	.64	.58	.50	.45
		(72 x 48)	Non-Res	.49		.33	.29	.59	.54	.25	.23	.65	.59	.47	.43
Western Select	PW	(48 x 48)	Res	.49		.33		.69	.63	.46	.43	.72	.65	.63	.57
		(48 x 72)	Non-Res	.49		.32		.64	.59	.44	.40	.71	.64	.60	.54
Western Select	SH	(36 x 60)	Res	.49		.34	.30	.62	.56	.27	.25	.65	.58	.50	.45
		(48 x 72)	Non-Res	.49		.33	.29	.59	.54	.25	.23	.65	.59	.47	.43
273P	PD	(72 x 82)	Res	.48		.33	.29	.62	.56	.27	.25	.65	.58	.51	.45
		(72 x 96)	Non-Res	.48		.32	.29	.58	.53	.25	.23	.64	.57	.46	.41

Sound Transmission Ratings

Window	Glazing Combination	STC Rating
110 S	SL 3/16" Clear With 1/8" Clear	31
120 S	PW 3/16" Clear With 1/8" Clear	31
130 S	SH 3/16" Clear With 1/8" Clear	32

U-Value = Total U-Value of product
 Low-E = Guardian RL 7036 soft coat low emmissivity glass (e=0.036)
 SHGC = Total solar heat gain coefficient
 VLT = Visible Light Transmittance

All values tested/calculated with Low-E coating on surface #2 using Guardian Low-E, except PW

Current as of 8/18/2006