



NFRC Certified *Window Energy Performance Ratings*



PLATINUM

WW Model #	Style	Test size		U-Value Clear Glass	U-Value Low-E Glass	U-Value Low-E & Argon	SHGC Clear	SHGC Low-E	SHGC Low-E W/Grids	VLT Clear Glazing	VLT Low-E	VLT Low-E W/Grid	CR _e	Low-CR Argon	Low=e
210P	SL	(60 x 36)	Res	.50	.34	.29	.56	.29	.26	.58	.55	.49	55.0	62.0	
220P	PW	(48 x 48)	Res	.48	.33	.30	.63	.30	.28	.65	.57	.51	56.0	59.0	
230P	SH	(36 x 60)	Res	.50	.34	.29	.59	.29	.26	.61	.55	.49	55.0	62.0	
240P	CAS / AWN	(24 x 48)	Res	.43	.29	.26	.47	.23	.21	.49	.43	.38	58.0	62.0	
2090P	PD	(72 x 82)	Res	.48	.33	.29	.62	.27	.25	.65	.51	.45			

Note: Highlighted items are approved for 2009 Stimulus Tax incentives

U-Value = Total U-Value of product
 Low-E = Guardian RL 7036 soft coat low emmissivity glass (e=0.036)
 SHGC = Total solar heat gain coefficient
 VLT = Visible Light Transmittance
 CR = Condensation resistance

All values tested/calculated with Low-E coating on surface #2 using Guardian Low-E

Current as of 3/12/09

Sound Transmission Ratings

Window	Glazing Combination	STC Rating
210P	SL 3/16" Clear With 1/8" Clear	31
220P	PW 3/16" Clear With 1/8" Clear	32
230P	SH 3/16" Clear With 1/8" Clear	32

Estimated comparison approx SS=.26
 NOT certified DS=.28